NOTES:

1. SUBSTRATE: N-F2
2. COATING:

   S1 & S2: NONE
3. FOCAL LENGTH TOLERANCE: ±5%
4. CENTERING: 25 ARCMIN
5. RoHS: COMPLIANT
6. ASPHERIC SURFACE DESCRIBED BY THE FOLLOWING EQUATION AND COEFFICIENTS SHOWN IN TABLE BELOW

$$Z_{ASPH}(Y) = \frac{(1/RADIUS)*Y^2}{1+\sqrt{1-(1+k)*(1/RADIUS)^2*Y^2}} + D*Y^2 + E*Y^4 + F*Y^6 + G*Y^8 + H*Y^{10} + J*Y^{12} + L*Y^{14}$$

FOR INFORMATION ONLY:
DO NOT MANUFACTURE PARTS TO THIS DRAWING





SECTION A-A

COEFFICIENT TABLE	
COEFFIECIENT	S1
SEMI-DIAMETER	9.000000E+00
(1/RADIUS)	0.191939E+00
k	-2.616910E+00
D	0.000000E+00
E	0.000000E+00
F	0.000000E+00
G	0.000000E+00
H	0.000000E+00
J	0.000000E+00
L	0.000000E+00

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE
DIMENSIONS ARE FOR REFERENCE ONLY

	S1	S2
SHAPE	CONVEX	PLANO
SURFACE QUALITY	As Molded	As Molded
CLEAR APERTURE	Ø14.40	Ø14.40
BEVEL	PROTECTIVE AS NEEDED	PROTECTIVE AS NEEDED

EFL: 8mm		Edmund Optics®	
BFL: 4.11mm			
THIRD ANGLE PROJECTION		TITLE	18mm DIA. X 8mm FL, UNCOATED MOLDED ASPHERIC CONDENSER LENS
ALL DIMS IN	mm	DWG NO	34460
			SHEET 1 OF 1