NOTES:


- 1. SUBSTRATE: FUSED SILICA
- 2. SURFACE S2 TO BE PARALLEL TO S1 TO WITHIN <3 ARCMIN
- 3. COATING (APPLY ACROSS COATING APERTURE)


\$1: R(AVG) \geq 98% @ 340-488nm @ 0° AOI R(AVG) \geq 98% @ 320-450nm @ 45° AOI FOR ALL POLARIZATION R(AVG) \geq 98% @ 320-450nm @ 45° FOR S-POLARIZATION

S2: NONE



5. ROHS COMPLIANT





FOR INFORMATION ONLY: DO NOT MANUFACTURE PARTS TO THIS DRAWING

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE DIMENSIONS ARE FOR REFERENCE ONLY

SHAPE	\$1 PLANO	\$2 PLANO			Edmund Optic	CS®
SURFACE QUALITY	10-5	COMMERCIAL POLISH			MIRROR BROADBAND 320-450nm 19.1m	nm DIA
SURFACE FLATNESS	λ/10	N/A	THIRD ANGLE PROJECTION	TITLE	WIIRROR BROYED (140 320 430) 111 17:111	ШПОЛ
MIN CLEAR APERTURE	Ø17.19	N/A				CUEET
BEVEL	PROTECTIVE AS NEEDED	PROTECTIVE AS NEEDED	ALL DIMS IN mm	DWG NO	39204	SHEET 1 OF 1