## NOTES:

## 1. SUBSTRATE:

CRYSTAL QUARTZ

2. COATING (APPLY ACROSS CLEAR APERTURE)

\$1 & \$2: R(abs)<0.2% @1030nm


DAMAGE THRESHOLD: >10 J/cm<sup>2</sup> @10ns @1064 nm


3. SURFACE S1 TO BE PARALLEL TO SURFACE S2 TO WITHIN <3 ARCSEC


4. RETARDANCE: λ/4 ±λ/300 @ 20° C

5. TRANSMITTED WAVEFRONT: <λ/10 @ 632.8 nm

6. ROHS COMPLIANT







**SECTION A-A** 

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE DIMENSIONS ARE FOR REFERENCE ONLY

## **PARTS TO THIS DRAWING**

DO NOT MANUFACTURE PARTS TO THIS DRAWING		<b>Edmund Optics®</b>					
CLEAR APERTURE	\$1 Ø8.0	\$2 Ø8.0	THIRD ANGLE PROJECTION	$\bigoplus$	TITLE	12.7mm Dia. 1030nm λ/4 Quartz Wavep Zero Order	olate
SURFACE QUALITY	10-5	10-5	ALL DIMS IN	mm	DWG NO	16886	SHEET 1 OF 1