

NOTES:

- 1. SUBSTRATE: N-BK7
- 2. S2 TO BE PARALLEL TO S1 TO WITHIN <1 ARCMIN
- 3. COATING (APPLY ACROSS COATING APERTURE) \$1 & \$2: VIS 0° (425-675nm) R(AVG) ≤0.4% @ 425 675nm



- 5. ROHS COMPLIANT
- 6. SURFACE FLATNESS (P-V): λ/4 (per inch over clear aperture)





PARTS TO THIS DRAWING

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE DIMENSIONS ARE FOR REFERENCE ONLY

			_
	\$1	\$2	
SHAPE	PLANO	PLANO	
SURFACE QUALITY	60-40	60-40	THIRD ANGLE PROJECTION
WAVELENGTH RANGE	425 - 675 nm	425 - 675 nm	
BEVEL	PROTECTIVE AS NEEDED	PROTECTIVE AS NEEDED	ALL DIMS IN

		Edmund Optics ®		
THIRD ANGLE - PROJECTION		TITLE	150mm DIA., 10mm THICK, VIS 0° COAT N-BK7 WINDOW	ED λ/4
ALL DIMS IN	mm	DWG NO	17300	SHEET 1 OF 1