

## Coherent® High Sensitivity Optical Power Sensor 1098318 | 1000:1 Attenuator

See More by [Coherent®](#)



#59-970 Coherent® High Sensitivity Optical Power Sensor 1098318 | 1000:1 Attenuator

Stock **#59-970** [CONTACT US](#)

⊖ 1 ⊕ C\$805<sup>00</sup>

**ADD TO CART**

Volume Pricing	
Qty 1+	C\$805.00 each
Need More?	<a href="#">Request Quote</a>

Product Downloads

### SPECIFICATIONS

#### General

±5 Calibration Uncertainty (%):

[#59-979](#) and [#59-980](#) Compatible Laser Models:

## Optical Properties

400 - 1800 **Wavelength Range (nm):**

1100:1 to 950:1 **Min. to Max. Attenuation:**

## Electrical

100 **Maximum Incident Power Density (mW/cm<sup>2</sup>):**

## Regulatory Compliance

[Compliant](#) **RoHS 2015:**

[Compliant](#) **Reach 224:**

[View](#) **Certificate of Conformance:**

## PRODUCT DETAILS

- Utilize Silicon or Germanium Detectors
- Ideal for nW to Low mW CW Laser Measurements
- Removable Light Shield
- Compatible with [Coherent® Laser Power and Energy Meters](#)

Coherent® High Sensitivity Optical Power Sensors are semiconductor sensors designed for nanowatt to low milliwatt continuous wave laser measurements. These semiconductor sensors are available for detection from the ultraviolet to the infrared, and feature a removable light shield. An attenuator is also available that will boost power up to 5W.

**Note:** OP-2 sensors are compatible with the LabMax-Pro ([#35-203](#)), LabMax-TOP/TO ([#88-412](#)), FieldMaxI-TOP/TO ([#66-277](#)), and FieldMate ([#59-978](#)) meters.