

[See all 9 Products in Family](#)

10X Nikon CF IC Epi Plan DI Mirau Interferometry Objective

See More by [Nikon](#)



10X Nikon CF IC Epi Plan DI Interferometry Objective, #59-312

Stock **#59-312** **20+ In Stock**

C\$5,376⁰⁰

ADD TO CART

Volume Pricing	
Qty 1+	C\$5,376.00 each
Need More?	Request Quote

Product Downloads

General

Model Number:
MJL40101

Compatible Tube Lens Focal Length (mm):
Focal Length: 200mm

Type:
Microscope Objective

Style:
Infinity Corrected

Manufacturer:

Physical & Mechanical Properties

2.00 **Field of View (mm):**

37.60 **Length excluding Threads (mm):**

28 **Maximum Diameter (mm):**

125.00 **Weight (g):**

Optical Properties

0.64mm **Horizontal Field of View, 1/2" Sensor:**

0.88mm **Horizontal Field of View, 2/3" Sensor:**

20.00 **Focal Length FL (mm):**

10X **Magnification:**

0.30 **Numerical Aperture NA:**

0.92 **Resolving Power (μm):**

3.04 **Depth of Field (μm):**

2.00 **Field of View, 20 Diameter Field Eyepiece (mm):**

2.5 **Field of View, 25 Diameter Field Eyepiece (mm):**

7.4 **Working Distance (mm):**

25 **Field Number (mm):**

45 **Parfocal Length (mm):**

N/A **Immersion Liquid:**

Sensor

2/3" **Maximum Sensor Format:**

Threading & Mounting

RMS / 20.32mm x36 TPI **Mounting Threads:**

Regulatory Compliance

[Compliant](#) **RoHS 2015:**

[View](#) **Certificate of Conformance:**

Product Details

- Suitable for Non-Contact Optical Profiling
- Mchelson and Mirau Objectives Available
- Infinity Corrected 200mm Tube Lens Design

Nikon Interferometry Objectives are used in non-contact optical profile measurement devices to obtain surface maps and surface measurement parameters. They can be used to examine surface topography with very high precision—to within a fraction of the wavelength of light. In these objectives, a light beam passes through a beamsplitter, which directs the light to both the surface of the sample and a built-in reference mirror. The light reflected from these surfaces recombines and a fringe interference pattern is formed. Nikon Interferometry Objectives are available in magnifications ranging from 2.5X to 100X.

The Mchelson objectives provide comparatively longer working distances, wider fields of view and larger depth of field, whereas the Mirau objectives are used in applications requiring higher magnification and/or numerical apertures. Use of the Nikon 200mm tube lens ([#58-520](#)) allows these objectives to be integrated to a C-Mount camera.