

120 MHz Fiber Coupled Optical Reciever Module



Stock **#87-324** CLEARANCE **5 In Stock**

-

1

+

C\$261^{.80}

ADD TO CART

Volume Pricing	
Qty 1+	C\$261.80 each
Need More?	Request Quote

Product Downloads

Optical Properties	
1310 - 1550	Wavelength Range (nm):
50/125/245/900	Fiber Diameter (µm):
Sensor	
25.00	Dynamic Range (dB):
Electrical	
	Sensitivity (dBm):

Hardware & Interface Connectivity

FC/PC

Connector:

Regulatory Compliance

[View](#)


Certificate of Conformance:

Product Details

- High Sensitivity and Overload Power with Wide Dynamic Range
- Designed for Bandwidths of 3MHz and 120MHz and Wavelength Ranges of 1310 – 1550nm
- Ideal for Biomedical, Industrial, or Telecommunication Optical Sensor Systems

Fiber-Coupled Optical Receiver Modules are ideal for use in biomedical optical sensor systems or for industrial and telecommunication sensing applications. Fiber-Coupled Optical Receiver Modules feature high sensitivity and high overload power, in addition to wide dynamic ranges. These receiver modules are designed for use in common telecommunication wavelength ranges.

Technical Information



Pin	Function
1	-5V detector bias
2, 6, 9, 11	No connection
12, 13, 14	No connection
3, 5, 8	Ground
4	-5V (LDFR = NC)
7	Output
10	+5V