

[See all 65 Products in Family](#)

Basler ace2 a2A2840-48umPRO Monochrome USB3 Pro Camera

See More by [Basler](#)



Basler ace2 USB 3.0 Cameras (Front)



Stock **#75-008** [CONTACT US](#)

- 1 + **C\$2,023⁰⁰**

ADD TO CART

Volume Pricing	
Qty 1+	C\$2,023.00 each
Need More?	Request Quote

Product Downloads

Monochrome **Spectrum:**

General

Monochrome Camera **Type:**

a2A2840-48umPRO **Model Number:**

Manufacturer:

Basler

Camera Series:

ace2

Physical & Mechanical Properties

Dimensions (mm):

42.8 mm X29 mm X29 mm

Weight (g):

90

Housing:

Full

Sensor

Sensor Format:

2/3"

Resolution (Megapixels):

8.10

Frame Rate (fps):

48.00

Pixels (H x V):

2,840 x2,840

Pixel Size, H x V (µm):

2.74 x2.74

Sensing Area, H x V (mm):

7.78 x7.78

Imaging Sensor:

Sony IMX546

Type of Sensor:

Progressive Scan CMOS

Shutter Type:

Global

Pixel Depth:

8/10/12 Bit

Exposure Time:

hardware trigger & freely programmable

Dynamic Range (dB):

70.2 dB

Machine Vision Standard:

USB 3.0 Vision, GenICam

Electrical

Power Consumption (W):

3.6

Hardware & Interface Connectivity

Interface:

USB 3.0

Connector:

USB 3.0, Micro-B

Power Supply:

Via USB 3.0 interface or 12-24 VDC

GPIOs:

1 opto-coupled input line, 2 general purpose I/O (GPIO) lines

Synchronization:

Hardware Trigger (GPIO), Software Trigger, or Free Run

Interface Port Orientation:

Back Panel

GPIO Connector Type:

M8 6-pin

Threading & Mounting

Mount:

C-Mount

Mounting Threads:

1/4-20 with Tripod Mount Adapter #16-641

Environmental & Durability Factors

Operating Temperature (°C):

-10 °C - 50 °C

Regulatory Compliance

Certificate of Conformance:


[View](#)

Product Details


- USB 3.0 with SONY Pregius S Sensors up to 24MP and 160 fps
- Proven Compact Housing (29 x 29mm)
- Powerful Computer Vision Feature Set with Optional Beyond Features
- [Basler ace USB 3.0 Cameras](#) Also Available

Basler ace2 USB 3.0 Cameras are available in two versions that provide optimized hardware design, proven compact and robust housing, and state of the art CMOS sensor technology with excellent image quality from Sony's 2nd-Gen Pregius, 3rd-Gen STARVIS, or the latest 4th-Gen Pregius S sensors. These second-generation Ace cameras include all of the components of the first-generation Ace cameras along with integrated features such as a status LED, removable IR cut filter, and robust MB connector. The Basler ace2 USB 3.0 Camera Basic version offers excellent price to performance ratio with powerful Computer Vision feature set, while the Pro version unlocks unique advanced Beyond features such as Pixel Beyond and Compression Beyond for maximum performance to meet with demanding application requirements. These cameras include the industry proven Basler Pylon SDK Software and Driver and conform to GenICam (USB3 Vision) standards, making them a fast and cost-effective solution to software integration. Basler ace2 Cameras are available in both USB 3.0 and GigE interfaces and are ideal for a wide range of applications such as factory automation and industrial robotics.


Technical Information




IMX676 Sensor QE Curve



IMX900 Sensor QE Curve



GMAX2505 Sensor QE Curve



IMX546 Sensor QE Curve



IMX545 Sensor QE Curve



GMAX2509 Sensor QE Curve



GMAX2518 Sensor QE Curve



IMX547 Sensor QE Curve



E2525A Sensor QE Curve

Calibration Services

