

[See all 12 Products in Family](#)

## Belt Driven Stage, Metric Breadboard Mounting Clamps

See More by [Zaber™](#)



Stock #23-234 **1 In Stock**

1  C\$64<sup>00</sup>

**ADD TO CART**

### Volume Pricing

Qty 1+	C\$64.40 each
Need More?	<a href="#">Request Quote</a>

### Product Downloads

#### General

Metric **Type:**

Zaber Technologies Inc. **Manufacturer:**

Sold in Pairs **Note:**

#### Threading & Mounting

**Mounting Threads:**  
(2) M4, (1) M6 S.H.C.S. Counter Bore Holes

## Regulatory Compliance

Compliant

RoHS 2015:

[View](#)

Certificate of Conformance:

Compliant

Reach 247:

## Product Details

- Designed for Use with Most 40mm T-Slot Extrusion Framing Systems and Accessories
- 500mm and 1000mm Long Travel Lengths Available
- Controlled Manually or via RS-232 Serial Interface
- Integrated 400 Counts per Revolution (CPR) Motor Mounted Encoder

Zaber™ T-Slot Extrusion Belt Driven Stages are computer-controlled stages based on a modular, expandable, T-Slot extrusion structure. The stages are compatible and easily integrated with most T-Slot extrusion framing systems. Zaber™ T-Slot Extrusion Belt Driven Stages can be controlled by the [Zaber™ Programmable Joystick Controller](#) (sold separately), a computer using an optional RS-232 or USB data cable, or manually with the knob integrated into the motor unit. The stage mounting platforms include 6X.M4 x0.7 mounting holes on a 25mm grid. Each stage features rotary quadrature encoders integrated into the stepper motor, with 400 Counts per Revolution (CPR) encoder resolution. The integrated rotary encoder provides closed-loop control and slip/stall detection and recovery.

**Note:** 24-48 VDC universal power supply (required), data cables for daisy chaining, and computer interface cables (USB or RS-232) are sold separately as accessories.