

Hamamatsu H11890-01 | 8mm, 230-870nm, Photon Counting USB PMT Module

See More by [Hamamatsu](#)



Hamamatsu USB-Powered Photon Counting PMT Modules

Stock **#14-799** **1 In Stock**

⊖ 1 ⊕ C\$5,467⁰⁰

ADD TO CART

Volume Pricing	
Qty 1+	C\$5,467.00 each
Need More?	Request Quote

Product Downloads

General

Photon Counting **Type:**

H11890-01 **Model Number:**

Multialkali Photocathode **Note:**

1 - 10,000 (PC Control) **Counter Gate Time (ms):**

Physical & Mechanical Properties

54 **Weight (g):**

40 x 22 x 48 **Dimensions (mm):**

Optical Properties

230 - 870 **Spectral Response (nm):**

400 **Peak Response Wavelength (nm):**

20 **Pulse Pair Resolution (ns):**

Electrical

Typical: 600
Max: 1000 **Dark Count (s⁻¹):**

Hardware & Interface Connectivity

USB Powered **Power Supply:**

Environmental & Durability Factors

+5 to +40 **Operating Temperature (°C):**

-20 to +50 **Storage Temperature (°C):**

Regulatory Compliance

[View](#) **Certificate of Conformance:**

Product Details

- Plug-and-Play Photon Counting via USB
- 8mm Effective Area
- Programmable with C++ or LabVIEW

Hamamatsu USB-Powered Photon Counting Photomultiplier Tube (PMT) Modules consist of a PMT, a high speed photon counting circuit, and a high voltage power supply. These photon counting heads are powered and operated through USB connection to a computer, providing plug-and-play functionality for photon counting measurement. Each PMT module ships with device drivers, DLL, sample photon counting software, and sample code for C++ and LabVIEW. Hamamatsu USB-Powered Photon Counting PMT Modules are used in medical applications including blood inspection devices, time-correlating single photon counting, and general research applications requiring photon counting. USB PMT Modules covering the UV, visible, and near-infrared (NIR) are available with two photocathode options, super-bialkali for enhanced quantum efficiency in the visible spectrum or multi-alkali for extended sensitivity into the NIR.

Note: PMT Modules are extremely light sensitive and exposure to ambient room light during operation will permanently damage the module. Housings are also fragile and will be permanently damaged if dropped. Damages due to above reasons are not covered under warranty or return policies.