

Metric Spatial Filter



Metric Spatial Filter, #57-739

Stock **#57-739** **14 In Stock**

⊖ 1 ⊕ C\$1,834⁰⁰

ADD TO CART

Volume Pricing

Qty 1+	C\$1,834.00 each
Need More?	Request Quote

Product Downloads

General

Adjustable - Linear (XYZ) & Tilt **Type:**

Pinhole **Type of Optics:**

Note:
Requires one pinhole aperture and microscope objective

Physical & Mechanical Properties

Black Anodized Aluminum **Construction:**

XY: ±1.5, Z: ±3
Linear Travel (mm):

2.5 (XY)
Linear Travel Resolution (µm):

±2
Base Tilt Angle (°):

Hardware & Interface Connectivity

Differential Micrometer (XY)
Type of Drive:

Threading & Mounting

M6 x 1.0
Compatible Post:

Regulatory Compliance

Exempt
RoHS 2015:

View
Certificate of Conformance:

Contains SVHC(s)
Reach 247:

Product Details

Metric Spatial Filters are only compatible with the following objectives: DIN Achromatic 4X (#36-131), DIN Micro-Plan 4X (#38-341), DIN Achromatic 4X (#43-902), DIN Plan 4X (#67-706), and the JIS Achromatic 10X (#30-046).

- X-Y Micrometer Translation
- Gimbal Tilt Control for Fiber Alignment
- Z-Axis Translation for Objective Mount

Our Metric Spatial Filters are designed to ease fiber optic and pinhole system integration. With ±1.5mm micrometer driven X-Y translation, 2.5µm resolution, and an objective mount with 10mm Z-axis translation, these Metric Spatial Filters are ideal for a range of DIN and JIS standard objectives. The fiber optic metric spatial filter provides easy connection for fiber optics with an FC termination and features gimbal tilt control for fiber alignment with a ±2° adjustable angle range. The pinhole metric spatial filter includes a pinhole adapter for integrating mounted and unmounted pinholes.

Note: Metric Spatial Filters are only compatible with the following objectives: DIN Achromatic 4X (#43-902), DIN Plan 4X (#67-706), and the JIS Achromatic 10X.

Technical Information

