

[See all 11 Products in Family](#)

Sill Optics 1030-1090nm 1X - 8X Variable Beam Expander, S6EXZ5076-328

See More by [Sill Optics](#)



Stock #70-162 **2 In Stock**

⊖ 1 ⊕ C\$3,367⁰⁰

ADD TO CART

| Volume Pricing | |
|----------------|-------------------------------|
| Qty 1-4 | C\$3,367.00 each |
| Qty 5+ | C\$3,031.00 each |
| Need More? | Request Quote |

Product Downloads

General

| | |
|-----------------------------------|----------------------|
| S6EXZ5076-328 | Model Number: |
| Beam Expander | Type: |
| Continuous Variable Magnification | Style: |

Physical & Mechanical Properties

Length (mm):

162.00

Weight (g):

0.60

Housing Diameter (mm):

58.00

Pointing Accuracy (mrad):

<1

Optical Properties

Entrance Aperture (mm):

10.30

Exit Aperture (mm):

31.00

Expansion Power:

1X - 8X

Substrate:

Fused Silica

Transmission (%):

>97

Coating:

1064

Design Wavelength DWL (nm):

1064

Wavelength Range (nm):

1030 - 1090

Coating Specification:

1030nm - 1090nm R < 0.20% - low absorption

Damage Threshold, By Design:

5.0 J/cm² per 1ns pulse at 50Hz

Divergence Adjustment:

Rotating Optics

Threading & Mounting

Mounting Threads:

C-Mount

Regulatory Compliance

Certificate of Conformance:

[View](#)

Product Details

- 1X–3X and 1X–8X Variable Magnification
- High Damage Thresholds up to 5.0 J/cm² (1ns, 50Hz)
- [Motorized Magnification](#) Versions Available

Sill Optics Variable Beam Expanders are designed to optimize focus diameter, focus position and beam propagation within a laser system. All optical elements within these beam expanders are constructed from fused silica substrates featuring a special low-absorption coating to minimize thermal effects. These beam expanders can withstand the high thermal strain of small beam diameters and provide stable and reliable performance while utilizing high average or high peak power lasers. Sill Optics Variable Beam Expanders are available for use with 355nm, 532nm, and 1064nm design wavelengths and feature high damage thresholds for pulsed lasers up to 5.0 J/cm² (1ns, 50Hz). These beam expanders are ideal for high power laser applications where magnification changes may be required, such as prototyping, solar cell manufacturing, confocal microscopy, or R&D.